



**GÜNTHER**



# **SPLITTER X2**

Mobile 2-fraction spiral shaft screen  
for difficult to screen material





## SPLITTER X2

### Processing in perfection

The chain-mobile SPLITTER X2 with its stable and robust SPLITTER TWIN WAVE screening deck is the separation expert for heavy, sticky and partly unshreddable material (stones, clay, contaminated soils for landfilling). Due to the trough-shaped design and the incline angle adjustment, the material remains on the screen deck for a sufficiently long time, is thus cleaned from adhering impurities and separates safely into two fractions. In addition to the production of a finished product, the SPLITTER X2 is also perfectly suited for preparing the material for subsequent processes.

Like all SPLITTER machines, the SPLITTER X2 is characterized by a wide range of adjustment options and a clog-free and wrap-free operation.

### Areas of application

- Stones
- Clay
- Contaminated soils for landfill
- Excavated soil
- Construction waste
- Mixed construction waste

### Your benefits in a nutshell:

- Highly efficient separation of difficult to screen material into 2 useful fractions.
- Quick and easy assembly and disassembly due to compact design with track chassis.
- Flexible adjustment of the discharge belts during operation. Reduced leakage due to one-piece and optimum discharge of the material streams.
- Thanks to the simple and intuitive, icon-based menu navigation, the machine can be operated with little training effort.
- Optimal feeder for downstream machine technology that processes classified and metered material processed.
- Low cleaning and maintenance requirements.
- Secure and powerful separation for wet or sticky material.
- Ready for use 365 days a year.



## The extreme

### Technical data

<b>Drive</b>	Diesel electric drive 80 kVA
<b>Material feed</b>	Metering hopper: 5 m <sup>3</sup> Feeding height: minimum 2.65 m (floor standing)
<b>Screening line</b>	Coarse screen L × W: 3.0 × 2.5 m / area: 7.5 m <sup>2</sup>
<b>Screen out</b>	Variant 1: 0...80/120 mm Variant 2: 0...40/55 mm
<b>Screen deck</b>	Spiral shaft screen: SPLITTER TWIN WAVE   Drive power 2 × 11 kW
<b>Discharge belts</b>	Discharge height of oversize grain belt is 3.3 to 4.2 m with infinitely variable inclination adjustment Discharge height of undersize curved belt is 2.8 m; 3-part, foldable; optional discharge right or left
<b>Throughput</b>	up to 200 t/h (depending on material)
<b>Machine weight</b>	32 t (excl. options)
<b>Machine dimensions</b>	L × W × H: 12.1 × 3.0 × 3.5 m
<b>Operation</b>	Touch panel and wireless remote control
<b>Options</b>	Feed grate for coarse pieces, various interchangeable screen decks



ANLAGENBAU GÜNTHER GmbH · Im Tiegel 7  
36367 Wartenberg · Telefon 06641 96 54 - 0  
[www.albg.eu](http://www.albg.eu) · [info@albg.eu](mailto:info@albg.eu)

